

Formed Thread Worm Drive Clamp(One Way)





32 (1.25°) MAX HOUSING





*Jolly size ordering codes vary as per SAE & IS/BS sizes.

Short Description

BAND.

Jolly One Way Serrated Clamp is designed as per German standard DIN 3017-01. Designed with one piece housing assembly this clamp is most suitable for applications with high mechanical load. This clamp contains threads on outer surface of band & smooth inner surface to ensure no damage to hose due to hose biting which makes this clamp suitable for soft nitrile hoses

Design Type Ordering Code: FS

DN equivalent	Ordering Code	Material Grade Option	
W3	M09	All parts	: SS 430
W 2	M21	Band Screw	: SS 430 : PCS

Ordering Code	Band Width (BW)		
B11	Band	: 13 mm max.	
B15	Band	: 9 mm max.	

Note: Clamps below dia 22 mm can be made in B11 ordering code.

Area of Application

 $\textbf{Automotive} \bullet \textbf{Filter Applications} \bullet \textbf{Industrial Applications} \bullet \textbf{Domestic Applications}$ Agricultural Applications

Ref. standard: DIN 3017 - 1

- One sided threads on band surface.
- · Smooth finish of inner surface.
- Eliminates damage to hose, in turn ensuring leak proof joint.

Jolly sizes

Jolly Size Ordering Code	Min Dia (in)	Max Dia (in)	Min Dia (mm)	Max Dia (mm)
J000	0.354	0.472	9	12
JOOM	0.433	0.630	11	16
100	0.512	0.787	13	20
JO	0.630	0.866	16	22
J100S	0.709	0.984	18	25
JOX	0.787	1.102	20	28
J1A	0.866	1.181	22	30
J137S	0.984	1.378	25	35
J1	1.181	1.496	30	38
J1X	1.181	1.575	30	40
J45A	1.378	1.772	35	45
J2A	1.496	1.969	38	50
J2	1.654	2.165	42	-55
J2X	1.772	2.362	45	60
13	1.969	2.756	50	70
J75A	2.165	2.953	55	75
J3X	2.362	3.150	60	80
J4	2.756	3.543	70	90
J4X	3.150	3.937	80	100
J110A	3.543	4.331	90	110
J5	3.740	4.528	95	115
J5X	3.937	4.724	100	120
J6	4.331	5.118	110	130
J575 S	4.921	5.709	125	145
J6X	5.512	6.299	140	160
',	Additional size	es are available a	as per enquiry.	

We reserve the right to make technical & dimensional modifications within Standard specification . UPC code made available on request. Packing Specification available.